

8 3 6 5 W - 2 6 7

1/2 HP AC CHAIN DRIVE WI-FI® GARAGE DOOR OPENER

A complete, reliable solution with powerful performance.



KEY FEATURES

VALUE
Package

CONSISTENT AND DEPENDABLE
Operation

WI-FI
Built In

INCLUDED ACCESSORIES:

MULTI-FUNCTION CONTROL PANEL®

Turns on garage door opener lights from inside the garage.



882LMW

(2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers or MyQ Light Accessories each.



893LM

WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



877LM

POWERFUL ADD-ONS:

MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



374UT

REMOTE LIGHT CONTROL

Enables home lighting control through a garage remote or a smartphone.



825LM

REMOTE LIGHT SWITCH

Replaces an existing wall switch to enable home lighting control with a garage remote or smartphone.



823LM

DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

RELIABLE

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY LIFETIME MOTOR, 1-YEAR PARTS.

SECURE

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

MyQ TECHNOLOGY ALLOWS USERS TO KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

PRODUCT GUIDE 8365W-267

1/2 HP AC CHAIN DRIVE WI-FI
GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR



- 1/2 Horsepower AC
- 1,625 RPM
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL Listed
- 4' Power Cord (3-Prong)

MECHANICS



- **Steel Chassis, T-Rail and Trolley**
- **Full Chain Drive Mechanism** (16:1 Gear Reduction and Adjustable Door Arm)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup
- **AC Wi-Fi Logic Board** with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)

7.25"



18.25"

10.5"

DIMENSIONS

| Rail Options | 7' | 8' | 10' |
|------------------|------|------|------|
| Installed Length | 128" | 140" | 164" |
| Max. Opening | 7'6" | 10' | 10' |

Headroom Clearance Required: 2"

7"

Per second
for door
to move
upward

SPEED

7"

Per second
for door
to move
downward

STANDARD SPECS.

SECURITY

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -35°F to 150°F

SECURITY+ 2.0®

(2) 3-Button Remote Controls (893LM) and Wireless Keyless Entry (877LM)

- Remote Controls: 310, 315 and 390 MHz Tri-Band*
- Keyless Entry: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only.

ENCRYPTED CONTROLS

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

SMART

MyQ® RADIO

902-928 MHz
50-Channel FHSS
(Frequency Hopping Spread Spectrum)

- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER*)

*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING



- Max. 2 100-Watt Lightbulbs
- Solid-State Light Delay
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

SHIPPING.

SHIPPING WEIGHT (in lbs.)

21
HEAD20
RAIL (7')

CARTONS (2)

CARTON 1: 20" x 12" x 10"

- Garage Door Opener Head (8365W)
- Multi-Function Control Panel (882LMW)
- (2) 3-Button Remote Controls (893LM)
- Wireless Keyless Entry (877LM)
- The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation (with Select Accessories)[†]
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 24 Remote Controls, 2 Wireless Keyless Entry Systems and 16 MyQ Devices

